

BERNINA®




Service manual

BERNINA 1090

(Supplement to service manual 1120 / 1130)

Safety Regulations



Attention

All electrical and electronic components operate at dangerous voltages. The mains plug must be withdrawn before making any adjustments to the machine. Wait at least 30 seconds afterwards (capacitor discharge).

Impressum

Authers: P. Kenyon
T. Kalberer

Graphics: F. Rapold

Typeset and printed:
by Bodan AG, Kreuzlingen

Contents (Supplement to service manual 1130/20)

	Page
Technical data	5
Description of Print L-1230	6
Print A-KAO	6
Print S-KAO	6
Block schematic model 1090	7
Plug connections	8
Print A-KAO	9
Print S-KAO	10
Print L-1230	11
Diagnosing instructions	12
Test adapter L-4200	13
Power supply – 4200	14
Service panel – 1090	15
Test programme with service-panel	16
Warning against dangerous voltages	17
Starting the service programme	17
Ending the service programme	17
Diagnosis	18 + 19
Test A L-1230	20
B Print L-1230 / R-4200 (Drive signal)	21
C Connection S-KAO / L-1230	22
D Mains cord (cord reel)	23
E Connection of print S-KAO / foot control unit	24
F Print P-4200	25
G Complete light holder	26
H ₁ Step motors:	27
○ Print S-KAO	
○ Hall-sensors	
H ₂ ○ Position Hall-sensor S.L.	28
○ Position Hall-sensor S.B.	
I Step motors pinning position	29
K Foot control unit	30
L Foot control digital/analog	31
M Print A-KAO	32
Print S-KAO	
Print L-1230	
N Ret-button	33
O Equalization of the forward/reverse feed	34
P Bobbin winder motor	35
Q Sewing-off:	36
○ Stitch length	
○ Stitch width	
○ Needle position L.C.R.	
○ Long stitch	
R Setting min. and max. position of SL and SB	37
Function test	38 + 39

Important:


A comparison of the models 1090 and 1130 is not made as from a technical point of view, they are identical.

All gauges, instruments, adjustments etc, which are applicable to model 1130 / 1230 are also valid here. BERNINA has only changed the test programme which also simplifies things for you.

These instructions are to be used in conjunction with the service manual cl. 1130.

This manual remains the property of our company, reproduction, publication or information to a third party without our written approval is forbidden.

FRITZ GEGAUF LTD.,
Manufacturers of BERNINA Sewing-Machines
Steckborn (TG) Switzerland



Technical data BERNINA model 1090

Stitch length max. forward 5 mm
max. reverse 5 mm

Increment 0-1 0,05 mm
1-3 0,1 mm
3-5 0,2 mm

Max. stitch width 5,5 mm

Increment 0,1 mm

Needle system 130/705 H

Adjusting needle 130/705 H/TCN

Hook system BERNINA CB= Central bobbin

Lowest point of needle bar=0 degree

Presser foot height=7,5 mm

Darning foot height=0,5 mm

Automatic long stitch 10 mm/2:1

Working space 105×195 mm

Overall length 375 mm

Overall width 184 mm

Overall height 350 mm

Motor 90 W

No of stitches per/min. min.-max. 120-1050/min

reduced min.-max. 120-600/min

Sewing light: bulb 2×6 V/4 W

Weight 10,5 kg

Features and functions

Needle position 5

Zig-zag and stitch length (freely adjustable)

Automatic basis adjustments

Basic marking LED

LED display for stitch length and width, manually adjusted

LED display for presser foot

Upper needle stop (general)

Lower needle stop (general)

Needle positioning upper/lower with foot pedal

Permanent reverse sewing

Buttonhole 3 step

Automatic long stitch

Balance for forward and reverse feed

Clear switch

Single pattern

Mirror image

Stitch pattern extended, stitch density remains constant

2 needle limiter

Memory: Capacity 5 units

8 practical stitches without reverse motion

6 practical stitches with reverse motion

6 decorative stitches without reverse motion

8 decorative stitches with reverse motion

28 number of stitch patterns

LED control for programmed pattern

Main switch

Separate light switch

Speed control using the foot control

Description

The electronics of the model 1090 sewing machine is essentially located on three large printed circuit boards; the power print L-1230, the control print S-KAO and the display print A-KAO (compare to the block schematic diagram). The tasks of the 3 units correspond to the known functions of L-4200, S-4200 and A-4200 prints from the model 1130.

L-1230 power print

The L-1230 power print is mounted above the motor on the rear side of sewing machine. The circuit components on the L-4200 have the following functions:

- *Motor control:*
The main motor control operates with the mains voltage. The main motor is a DC motor with pulse-width modulated speed control. The closed loop control circuit on the small R-4200 print is located on the power print. All circuit components for the motor control operate at dangerous voltage levels. The safety regulations must be adhered to.
- *Power supply:*
Generates the following D.C. voltages:
 - 30V for the step motors
 - 5V for the logic circuitry on the S-KAO and A-KAO prints
 - 6V for the sewing light
 - 30V for the bobbin winder motor
 Components are protected from overload, in the case of faults, by a fuse F 150. If a fuse blows only original replacement fuses, with the correct rating may be used.

A-KAO display print

The display section is mounted directly behind the operating control panel. The display and operating control elements are soldered onto the L-shaped printed circuit.

A time multiplex control allows the numerous LEDs and control elements to be connected to the open loop control on the S-KAO control print using only 21 connection lines.

S-KAO control print

The complete sewing machine control is located on the S-KAO control print. The S-KAO control print is located on the A-KAO print from the rear.

The most important control element is the microcomputer, and the power drive for the step motors. A new feature over model 1130 is that the bobbin winder motor is also controlled by the microprocessor. The bobbin winder motor speed can now be controlled from the foot control.

The S220 service switch on print S-KAO is a service aid. This switch has two positions: normal sewing operation, and service position. In the service position, several buttons and diodes on the display panel are assigned other functions.


This allows the service technician to execute necessary adjustment and testing functions using the display panel (refer to the special section service programme). The service switch must always be set into the sewing position for normal sewing operations.

The microcomputer on print S-KAO receives an analog signal from the foot control, which it then converts into a digital signal and transmits to print R-4200 as setpoint for the motor speed. The R-4200 print controls the motor speed to the speed specified by the S-print, using a setpoint – actual value comparison. When the foot control is released, the setpoint goes to zero, the brake is actuated from the microcomputer on the S-print via the R-4200 print, and the motor is rapidly braked.


Signal transfer between the S-KAO and R-4200 print is realised using a 4-pole cable. Signal transfer is realised through an opto-coupler providing electrical isolation and thus eliminating dangerous voltage levels from the foot control and the S-KAO control print.

The step motors are in random positions when sewing machine is switched on. Random values can also be in the microcomputer control memory. In order to have a defined state, the step motors are rotated into their calibrated position by a microcomputer command, and the position value is set to zero in the microcomputer memory. This starting state allows the selection and sewing of any stitch programme.


Model 1090 block schematic



Print A-KAO




S-KAO Print



Warning!

If print S-KAO has to be replaced, forward/reverse feed equalization with max. and min. position of the SB and SL Potentiometers must be carried out.

Print L-1230



Diagnostic instructions

- As opposed to model 1130, model 1090 is equipped with a service programme. The service programme is essentially designed for test and adjustment tasks.
- The diagnostic instructions should be adhered to for repair work. Reference should be made to the service programme for adjustment and equalization tasks.

Warning of dangerous voltage levels

Mains voltage (refer to print L-1230)

Circuit components on the L-1230 power print, the main motor and the cable drum, carry dangerous voltage levels. For your own safety, print L-1230 should only be touched after about 30 seconds after the mains voltage has been switched off, which is the time required by the capacitors to discharge after the mains plug has been removed.



Warning:

The sewing machine may only be connected to the mains supply when the chassis cover or the auxiliary cover is mounted. Work may only be carried out on the L-1230 print, main motor and cable drum when the mains plug has been withdrawn from the mains supply.

Electrically isolated low voltages (refer to print L-1230)

Several circuit components on the L-1230 print operate with electrically isolated low voltages (40 V or less). With the exception of the power print L-1230, the main motor and the cable drum, the other modules also operate with electrically isolated low voltages!
There is no danger involved in touching these components during operation.

Warning!

The following should be additionally observed when carrying out repair and adjustment work:


- Changing from the service programme to normal operation, and vice versa is only possible after changing the position of the service switch on the S-KAO print, and briefly switching off the mains voltage.
- The following adjustments should be made each time a S-KAO print is replaced:

Forward/reverse feed:	Service programme 6
Setting min. and max. position:	Service programme 3
- Switch off the mains voltage before touching and replacing the R-print.

Test adaptor L-4200

The power supply for electrical parts which are connected to print L-4200 and the main motor control are checked with the aid of the test adaptor.


- When all LEDs A to E light up, then the power supply for:
 - the step motors
 - the logic circuit
 - the sewing light
 is correct. Bobbin winder motor, LED E, *cannot* be tested.
- If only LED B doesn't light up, then the voltage for the logic is too high (more than 5,5 V).
- If only LED C doesn't light up, then voltage for the logic is too low (less than 4,5 V).
- When the motor switch is in the «on» position, the electric brake is released, the motor receives the desired value and will run at the set speed. LED F for the drive signal *must* be lit. Speed regulation is made by turning the potentiometer.
- When the motor switch is placed in the «off» position the signal returns to zero, and the electric brake should engage. The motor slows down to a stop. LED F *must* go out.



Power supply 4200

The power supply 4200 delivers current for the logic of print A-KAO and print S-KAO, the step motors, the sewing light. So that the whole machine can work with a safe low voltage, the main motor receives 30 V for safety reasons.

The power supply is useful when a mechanical adjustment is to be made, for which the rigidity plate with print L-1230 has to be removed.



When the mains switch is «on» the light indicates that the appliance is working. With the switch in the «off» position, the appliance is turned off.

Motor switch «on», the main motor will rotate slowly.


Adaptor print with cord ist pluggable.

There is a 400 mA fuse at the rear.

Important cl. 1090:

The connection for the bobbin winder motor is not used.

SERVICE-PANEL



Test-Programmes with Service-Panel

	What is to be tested	Test	Manual 1230 page	See also service manual 1130		
Test-Programmes ↑ Buttons 1 – 7 Service-Programmes ↓	1	Hall sensor position for stitch length	H ₂	28	Page 64 a (see also BERNINA Information No. 78)	
	2	Hall sensor position for stitch width	H ₂	28		
	3	* Setting min. and max. position of SB and SL	R	37		
	4	Sewing of	Q	36		
	5	Pinning position for step motors SL and SB	I	29		Section 49, resp. 53 pages 37 + 41
	6	Forward-reverse feed equalization	O	34		Section 41, pages 32 + 33
	7	Step motor / Hall sensors	H ₁	27		Page 64
	8	Digital / analog foot control	L	31		
	9	Drive signal	B	21		Page 58
	10	Ret button	N	33		
	11	Position indicator / P-print	F	25		Page 62
	12	Bobbin winder motor switch	P	35		

* This test must be carried out **whenever** the control chassis has been disassembled and reassembled.



Danger high level voltage!

Mains voltage (see print L-1230)

Circuits on the power print L-1230, the main motor and the cord drum operate at dangerous voltages. As some capacitors discharge approx. 30 seconds after pulling out the mains plug, you should wait this long before touching print L-1230.

Test-programm model 1090 (service operation)

1. Test-programme start

- Remove belt cover (service instructions model 1130, section 6).
- Set service switch on the S-print into service position (refer to Fig. S-KAO, page 10).
- Switch-on sewing machine / D.C. mains adaptor unit. The sewing machine is now in service programme no. 7 (step motors), move to and from with an acustical noise.
- Push clear button (min. 2 sec.).
- Mount service panel.

The sewing machine is now in the initial state of the service operation. The individual test programmes 1 to 7 can be selected from this state. The initial state can be selected by depressing the clear button.

- Testprogramme no. 3 can only be left after all 4 values have been memorized.

The following sensor signals can now be checked:

- Position indicator / P-print (test 5 model 1130).
- Foot control digital and analog (new).
- Drive signal (partially covered in test 1, test adaptor model 1130).
- Ret button (new).
- Adjust buttonholer potentiometer (partially section 42 model 1130).

Termination of the test-programme

- Switch off the sewing machine / D.C. mains adaptor.
- Bring the service switch on the S-print into the normal position.
The sewing machine can now be operated normally.

Attention:


- When changing from normal operation – Service operation – normal operation.
- Bring the service switch into the desired position.
 - Switch mains adaptor off and then on again.

	Fault	Possible fault on	Repair instructions
Diagnosis	Display panel and sewing light not illuminated Main motor not running Machine «dead»	<ul style="list-style-type: none"> - L-1230 print - Mains cable 	<ul style="list-style-type: none"> - Test A, resp. M - Test D
	Main motor does not rotate other functions OK	<ul style="list-style-type: none"> - L-1230 print - R-4200 print - S-KAO print - Foot control - Connection between S-KAO and L-1230 prints - Connection between S-KAO print and foot control - Main motor 	<ul style="list-style-type: none"> - Test A, resp. M - Replace R-4200 print after switching off mains voltage - Replace S-KAO print - Check control, replace bobbin winder motor foot control, if nec. test K, L - Test C - Test E - Check motor cable and plug - Replace motor
	Bobbin winder motor does not function, other functions OK	<ul style="list-style-type: none"> - S-KAO print - Bobbin winder 	<ul style="list-style-type: none"> - Test P - Replace print S-KAO - Replace complete bobbin winder
	Sewing light does not function	<ul style="list-style-type: none"> - Lamps - Lamp holder - Print L-1230 	<ul style="list-style-type: none"> - Replace lamps - Test G - Test A
	Step motors do not position	<ul style="list-style-type: none"> - Step motor print S-KAO - Connection between S-KAO and L-1230 prints 	<ul style="list-style-type: none"> - Test H₁, H₂ - Test C
	Front panel LED does not illuminate, however selected function is executed when button depressed	Print A-KAO	<ul style="list-style-type: none"> - Replace print A-KAO


	Fault	Possible fault on	Repair instructions
Diagnosis	Selected functions not executed when button depressed	<ul style="list-style-type: none"> – Print A-KAO 	<ul style="list-style-type: none"> – Replace print A-KAO, if malfunction still occurs, replace print S-KAO. Test with new S-KAO, print and old A-KAO print.
	Long stitch device does not function	<ul style="list-style-type: none"> – Print S-KAO – Long stitch device magnet 	<ul style="list-style-type: none"> – Replace print S-KAO – Replace magnet and adjust
	Reverse button does not function	<ul style="list-style-type: none"> – Print S-KAO – Print Ret-KAO 	<ul style="list-style-type: none"> – Start service test programme, depress reverse button, LED RET must illuminate, if not: replace print S-KAO or if nec. Ret print.
	Irregular stitch width or length	<ul style="list-style-type: none"> – Step motor 	<ul style="list-style-type: none"> – Test H₁, H₂
	Main motor stops after 5 seconds	<ul style="list-style-type: none"> – Print P-4200 – Print S-KAO 	<ul style="list-style-type: none"> – Test F – Replace print S-KAO
	No needle stop	<ul style="list-style-type: none"> – Print P-4200 – Print S-KAO – Print L-1230 	<ul style="list-style-type: none"> – Test F – Replace print S-KAO – Test A
	Stitch pattern no. 27 is too short or too long	<ul style="list-style-type: none"> – Feed equalization 	<ul style="list-style-type: none"> – Service-programme no. 6

What is to be tested	What to adjust	Normal condition
<p>Print L-1230/R-4200</p>	<ul style="list-style-type: none"> – Initial state of service operation (page 17) – Select test 4 (sewing-off) – Depress foot control 	<ul style="list-style-type: none"> – The LED «signal» is illuminated, the motor rotates.
<p><i>Repair instructions:</i> – If the LED «signal» M is not illuminated: A test should be conducted with a new R-print and the old L-print. If still faulty, then replace L-print and repeat test. If still faulty, replace S-print, and if necessary check the cable connection L-/S-print (refer to test C, page 22).</p>		

Test B (Service-Panel)


	What is to be tested	What to adjust	Normal condition
Test C	<p>Connection of print S-KAO to print L-1230.</p> <p>Flat cord 5 pol, red connectors Flat cord 4 pol, green connectors</p>	<ul style="list-style-type: none"> - Take out mains plug. a) Disconnect connectors from print L-1230 and S-KAO b) Check on the upper side of the connectors with a circuit tester or ohmmeter that each wire is continuous. c) Test every wire as described in b). 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> - High pitched tone! Cord ok. - Ohmmeter shows a small resistance, cord ok.
<p><i>Important:</i> If there is no high pitched tone, or the display of the ohmmeter wavers or shows infinite resistance, then the cord is defective. Replace connection.</p>			

Test D

What is to be tested	What to adjust	Normal condition
<p>Mains cord (cord reel)</p>	<ul style="list-style-type: none"> - Take out mains plug. a) Disconnect in a plug at P158 on print L-1230. b) Connect one end of the tester to the plug, then test every wire to check that a circuit can be made. 	<div style="text-align: right;">  </div> <ul style="list-style-type: none"> - Hith pitched tone! Cord ok. - Ohmmeter shows a small resistance, cord ok!


Important: If there is no high pitched tone, or the display of the ohmmeter wavers or shows infinite resistance, then the cord is defective. Replace cord reel.

Test E

What is to be tested	What to adjust	Normal condition
<p>Connection of print S-KAO to foot control plug.</p>	<ul style="list-style-type: none"> – Take out mains plug. a) Remove 2 pin black, foot control plug from print S-KAO. b) On the upper connection side of the print check with the circuit maker or ohmmeter that a circuit can be made between these and the foot control plug. c) Both connections on foot control plug have to be tested as described above. 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> – High pitched tone! Cord ok. – Ohmmeter shows a small resistance, cord ok.

Important: If there is no high pitched tone, or the display of the ohmmeter wavers or shows infinite resistance, then the cord is defective. Replace cord.

What is to be tested	What to adjust	Normal condition															
<p>Print P-4200</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">Test F (Service-Panel)</p>	<ul style="list-style-type: none"> - Initial state of service operation (page 17) a) Using the handwheel bring needle to lowest position. b) Rotate handwheel forwards and check table to the right <p><i>Important:</i> If the print does not function as required per the table, then repeat tests a) and b) using a new print. If there are still discrepancies then refit the old print, replace print S-KAO, and repeat tests a) and b).</p>	<ul style="list-style-type: none"> - LEDs SL, SB and stop not illuminated on the service panel <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">LED SL</td> <td style="text-align: center;">LED SB</td> <td style="text-align: center;">LED STOP</td> </tr> <tr> <td style="text-align: center;">on</td> <td style="text-align: center;">on</td> <td style="text-align: center;">off</td> </tr> <tr> <td style="text-align: center;">on</td> <td style="text-align: center;">on</td> <td style="text-align: center;">on</td> </tr> <tr> <td style="text-align: center;">off</td> <td style="text-align: center;">off</td> <td style="text-align: center;">on</td> </tr> <tr> <td style="text-align: center;">off</td> <td style="text-align: center;">off</td> <td style="text-align: center;">off</td> </tr> </table>	LED SL	LED SB	LED STOP	on	on	off	on	on	on	off	off	on	off	off	off
LED SL	LED SB	LED STOP															
on	on	off															
on	on	on															
off	off	on															
off	off	off															

	What is to be tested	What to adjust	Normal condition
Test G	Lamp holder	<ul style="list-style-type: none"> - Mains switch on. a) Switch on sewing light. 	<ul style="list-style-type: none"> - Sewing light burns.  <p>The diagram shows a circuit with two lamps, L1 and L2, connected in parallel. A switch, labeled 'S', is connected in series with the parallel combination of the lamps. The entire circuit is connected to a 2-pin green plug.</p>
<p><i>Important:</i> If the sewing light doesn't function and both bulbs are intact, then the connections from L1, L2 and S to the plug can be checked with the circuit tester or ohmmeter. The switch S can be tested by putting the test probes in the plug openings, and by switching on and off there must be continuity and blockage in the circuit. To be sure, the same test must be made with the 2-pin green plug. L1 and L2 can be tested for continuity on the plug openings. Faulty parts must be exchanged.</p>			

What is to be tested	What to adjust	Normal condition
Step motors, print S-KAO	<ul style="list-style-type: none"> - Initial state of service operation (page 17) - Select service test programme 7 	<ul style="list-style-type: none"> - Step motors rotate back and forth, feed dog and needle bar must move
<p>If a step motor does not rotate, then the fault can either lie with the step motor, or print S-KAO. The faulty components can be identified by swapping the connections (plug P208 with P207, step motors).</p>		
Hall sensors	<ul style="list-style-type: none"> - Initial state of service operation (page 17) Select service test programme 7 - Select service test programme 1 SL and 2 SB for Hall sensor position check (test H₂ page 28). 	<ul style="list-style-type: none"> - LEDs for the Hall sensors on the service panel should flash at the same frequency as the stepping motor motion
<p>If the check LED of the Hall sensors does not flash, then the fault can lie in the Hall sensor, the mechanical part or the step motor. Replace defective step motor (see manual 1130, pages 35 to 41).</p>		
	<ul style="list-style-type: none"> - Connect the removed motor and Hall sensor to print S-KAO and energize with the 4200 supply unit. - Manually slide magnet over the Hall sensor. - Select service test programme 1 for SL step motor. - Select service test programme 2 for SB step motor. 	<ul style="list-style-type: none"> - LED SL must illuminate - LED SB must illuminate
<p>If the LED does not illuminate, replace the Hall sensor and adjust the step motor to its zero position (service test programme 6, see test O).</p>		


Test H₁ (Service-Panel)


What is to be tested	What to adjust	Normal condition
<p>Pinning position of step motors: refer to section 49, or 53 model 1130 (pages 41 and 37).</p>	<ul style="list-style-type: none"> - Initial state of service operation (page 17) - Select service test programme 5 	<ul style="list-style-type: none"> - The step motors are activated to the step position for pinning.

Test I (Service-Panel)

What is to be tested	What to adjust	Normal condition
<p>Foot control digital/analog:</p>	<ul style="list-style-type: none"> - Start service-programme - Connect foot control to the machine. - Depress slowly forwards. 	<ul style="list-style-type: none"> - LEDs «analog and digital» are illuminated.
<p><i>Repair instructions:</i> – The s-print should be replaced if only the «analog or digital» LED is illuminated. – The foot control is defective if neither of the LEDs is illuminated (regulator or cable).</p>		

Test L (Service-Panel)

What is to be tested	What to adjust	Normal condition
<p>Print A-KAO Print S-KAO</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">Test M</p>	<p>Switch mains supply off</p> <ul style="list-style-type: none"> - Connect up the 4200 supply unit to the sewing light, main motor, connecting cable to print S-KAO (4-pole green, control signals), the connecting cable to print S-KAO (5-pole red, supply). - Switch-on supply unit - Check display panel - Start service programme (page 17). Select service test programme 7. 	 <ul style="list-style-type: none"> - For every button pressed, the matching LED will light up. - When an alteration in stitch length or stitch width (from basis value) is made, the matching LED display (SB / SL) «manual-alteration» must light up. - Step motors rotate back and forth. Check LEDs SL and SB flash at the same frequency as stepping motor motion.
	<ul style="list-style-type: none"> - Motor switch «on» 	<ul style="list-style-type: none"> - Motor runs
<p>Important: Print S-KAO must be replaced, and the test repeated if the display panel is not illuminated, or if step motors do not rotate. Replace print A-KAO if faults occur on the display panel.</p> <ul style="list-style-type: none"> - If the motor doesn't run, exchange the motor. 		<p><i>Directive:</i> If the above tests all function with the mains device, then the fault can only be in the L-print. See test A.</p>

What is to be tested	What to adjust	Normal condition
<p>Ret-Button (Reverse button)</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">Test N (Service-Panel)</p>	<ul style="list-style-type: none"> - Initial state of service operation (page 17) - Depress ret-button  <p style="text-align: right;">Ret-button</p>	<ul style="list-style-type: none"> - LED «Ret» is illuminated
<p><i>Repair instructions:</i></p> <ul style="list-style-type: none"> - LED «Ret» is not illuminated: - A check should first be made as to whether the switch is being actuated. If this is not the case, then the switch activator should be mechanically adjusted (travel increased) until the switch is actuated. The following procedure should be followed if the LED «Ret» is still not illuminated. - Remove the P203 2-pole red plug connection at the S-print. - Connect new Ret-print. - Manually actuate the switch, LED «Ret» illuminates. - Replace Ret-print. 		

What is to be tested	What to adjust	Normal condition										
<p>Equalization of the forward/reverse feed.</p> <p><i>Directive:</i> First of all the zero pos. of the stitch length crank must be checked (see chapter 2, page 40 Service-Manual cl. 1130).</p>	<ul style="list-style-type: none"> - Initial state of service operation (page 17) - Select Test-programme no. 6, in this programme - The stitch no. 23 or no. 27 and the buttonhole are active. The forward/reverse feed can now be equalized with the + and - buttons during sewing, and at full speed. - The neutral position is at value 4. The selected value is only then stored, when the clear button is actuated. (Normal value lies between 2 and 6). <div style="text-align: center; margin: 10px 0;"> <p>- BALANCE +</p> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">0</td> <td style="padding: 0 10px;"><4</td> <td style="padding: 0 10px;">4</td> <td style="padding: 0 10px;">>4</td> <td style="padding: 0 10px;">8</td> </tr> <tr> <td style="text-align: center;">○</td> </tr> </table> </div> <ul style="list-style-type: none"> LED 0: Value 0 - Reverse feed is longest LED <4: Value 1-3 LED 4: Value 4 - Neutral setting LED >4: Value 5-7 LED 8: Value 8 - Vorward feed is longest 	0	<4	4	>4	8	○	○	○	○	○	<ul style="list-style-type: none"> - The stitch pattern must be correct at all speeds.
0	<4	4	>4	8								
○	○	○	○	○								

Test O (Service-Panel)

What is to be tested	What to adjust	Normal condition
<ul style="list-style-type: none"> - Bobbin winder motor switch - Control of winder motor 	<p>Switch on winder motor</p>	<p>LED «winder» lights up</p> <p>Speed of winder must be able to be regulated.</p>

Test P (Service-Panel)

	What is to be tested	What to adjust	Normal condition
Test Q (Service-Panel)	Sewing off: The stitch length, width, LMR and the automatic long stitch (not the basting stitch).	<ul style="list-style-type: none"> - Initial state of service operation (page 17). - Select-service-programme 4. 	<ul style="list-style-type: none"> - The machine can now be sewn-off. L.C.R. Straight stitch Stitch length and stitch width can be adjusted Long stitch
<p>Note: If the normal condition ist not achieved then test M must be carried out first.</p>			

	What is to be tested	What to adjust	Normal condition
Test R (Service-Panel)	<ul style="list-style-type: none"> - Setting min. and max. position of stitch width and stitch length 	<ul style="list-style-type: none"> - Initial state of service-programme (page 17). - Select test-programme no. 3. 1. Turn stitch width knob to max. (5,5mm) press ENTER-button (SB) to memorize. 2. Turn stitch width knob to min. (0mm) press ENTER-button (SB) to memorize. 3. Turn stitch length knob to max. (5mm) press ENTER-button (SL) to memorize. 4. Turn stitch length knob to min. (0mm) press ENTER-button (SL) to memorize. - All 4 values are memorized. 	<ul style="list-style-type: none"> - The LED SB MAX will light up in field 3 b. - The LED SB MIN will light up in field 3 b. - The LED SL MAX will light up in field 3 b. - The LED SL MIN will light up in field 3 b. - Service-programme in its initial state.
	The test-programme can only be left when all 4 values have been memorized.	The order of the steps 1–4 is immaterial.	If an LED doesn't light up although a value has been memorized. This means that the knob is not at a minimum or maximum value.

What to adjust	Normal condition
Switch on <i>bobbin winder</i> Switch off <i>bobbin winder</i>	Bobbin winder runs Bobbin winder stops
Switch on <i>sewing light</i> Switch off <i>sewing light</i>	Sewing light comes on Sewing light goes out
<i>Main motor</i> Fully depress foot control Stop from fastest speed Press foot control backwards	Speed of sewing machine 1050 rpm Motor brakes, thread take-up lever is in its highest position Machine positions in lower needle position
<i>Reverse button</i> Sew forwards Press reverse button Release reverse button	Transport forward Transport reverse Transport forward
<i>Longstitch device magnet</i> Sew using automatic long stitch	Every second stitch is sewn
Depress foot control for a short time Press lower needle stop button  Depress foot control for a short time	Upper needle stop LED lights up Lower needle stop

Function-tests electronic

What to adjust	Normal condition
<p>Adjust the stitch width and stitch length with the knobs</p> <p>Select another stitch</p>	<p>Appropriate LED display (SB/SL manual adjustment) must light up.</p> <p>Both LED displays do not light up</p>
<p>To check the electrical transport equalization, sew using stitch 28</p>	<p>Sewn patterns must be closed</p>
<p>Press all function buttons and check LEDs</p>	<p>All LED's should light up</p>
<p>Press all stitch selection buttons.</p>	<p>The respective LED should light up. Basic values of stitch width and stitch length are displayed (LED)</p>

Function-test electronic

Appendix

Assembly of the operating chassis/A-Print and S-Print

- Turn the two potentiometers for stitch length (SL) and stitch width (SB) until both arrows are face to face (see drawing).
- Turn the operating knob for stitch length (SL) in the minimum position «0».
- Turn the operating knob for stitch width (SB) in the maximum position «5».
- Position the connection pins of the S-Print to the A-Print, and press together.
- Secure with the 4 securing screws.

